

STREET LIGHTING
CAR PARKS
PATHWAYS
INDUSTRIAL SITES
RECREATIONAL AREAS
MARINE INFRASTRUCTURE
CARAVAN & HOLIDAY PARK


Designed in Australia to meet the increasing demand for smart connected lighting infrastructure

the ASPIRE offers an environmentally friendly, off-grid connected solar option where traditional lighting is impractical or cost prohibitive






THE ASPIRE SERIES TAKES THE BEST OF ALL PREDECESSORS AND PUTS THEM INTO A SINGLE, HIGH QUALITY, ULTRA RELIABLE SOLAR LIGHT.










Established in Australia
2011, the company designs
and manufactures quality
solar street and pathway
illumination systems with
installations across Australia
and overseas.

Green Frog Systems is committed to the continual development of leading edge, sustainable solar lighting and energy storage advancements.



LED



Adjustable LED angle between 0° - 15° to control light throw & spill light direction with 28 x USA Made XP-G CREE LED. Maximum LED efficacy 187lm/W. 30W=5,610lm / 60W=11,220lm / 75W=14,025lm / 100W=18,700lm



SYSTEM PERFORMANCE

Full brightness all night operation (30W) for up to 14 hour a night with 5 nights battery backup even in overcast or rainy conditions. Tuned for optimum low light and winter performance

SOLAR PANEL



360° rotation with 0°-60° tilt. Impact resistant panel with edgeless frame design to prevent build up of dirt and avian fouling. 225W - 450W mono-crystalline panel(s) with class leading solar panel efficiency (21%), and a 25 year Warranty



PRODUCT DIFFERETIATORS

Panel can be landscape or portrait orientation requires only an allen key. The panel can also be paired easily with additional units - a single additional mounting arm can turn the 225W system into a 450W system

BATTERY & CHARGING



Up to 4 Replaceable GFS Advanced Cell LiFeP04 Batteries in the pole or underground @ 1474Wh. Batteries are housed in a puncture, impact, heat, water and fire resistant aluminium shell with quick release IP68 waterproof connectors



DIMMING OPTIONS

Programmable ON / OFF settings (1-14 hours) light dimming settings from 5%-100% with additional program to schedule ON time before dawn (1-4 hours)

WEATHER RESISTANCE



IP65 rated housing which is able to withstand full flood immersion. IP68 waterproof components and connectors throughout the unit. Proven performance in tropical, desert, beach front and flood prone locations



VANDAL RESISTANCE

High strength IK10 poly-carbonate lenses with a tempered glass impact resistant solar panel, The back of the solar panel is protected by a dual layer aluminium backing plate for added impact and linter resistance

^{*3} year full warranty plus 2 years pro rata warranty. Refer to tech data sheet





HEAD OFFICE

51 Langford St Pooraka. South Australia 5095

+61 8 7200 3909

info@greenfrogsystems.com.au greenfrogsystems.com.au

USA / AMERICAS

1919 McKinney Avenue, Suite 100, Dallas, Texas. 75201

+1 (214) 838-7010

info@greenfrogsystems.com greenfrogsystems.com